

## PRODUCT DATA SHEET

### Identification of the material and the supplier

Product: **INSULGLAZE**  
Recommended use: (see recommended uses below)  
Supplier: **Insultec Pty Ltd**  
ABN: 31 687 337 604  
Address: 18 Currawong Ave, Normanhurst NSW 2076  
Telephone: 1300 763 335  
Email: technical@insultec.com.au  
Website: www.insultec.com.au

Emergency Number: **13 11 26 (Poisons Information Centre)**

Date of SDS Preparation: June 2026

### Features

- Water clear acrylic, excellent resistance to UV.
- Very good durability.
- High resistance to finger marks, minerals, alkalis, grease etc.
- Very good self-cleaning properties.

### Recommended uses

- As a clear protective coating over masonry surfaces.
- As a sealer coat over Matt acrylics.
- As a sealer coat over Insulseal membranes.

### Surface Preparation

Apply only over clean, dry surfaces, which have been thoroughly cleaned or water blasted.

### Application

- For bare new or old masonry apply two coats by brush or airless spray, allowing four hours drying time between two coats.
- Over previously painted surfaces apply one or two coats by airless spray.
- Ensure that previously painted surfaces have been allowed to cure for at least 48 hours or a patchy finish may occur.
- Clean up with water when wet or solvents when dry.

### Coverage

- Approximately 4 - 6 sq.meters per liter.

### Packaging

- 20-liter pails.

Disclaimer: The data contained herein is based upon information, which the company believed to be reliable at the time of preparation of this data sheet. No responsibility can be accepted, or any express or implied warranty given where performance of the product is affected by surface preparation, method of application or any other circumstances beyond the control of this company.